

MINIFLEX® 3-BFN L-HD

보강판에 의한 견고성, 롱 액추에이터, 저배 (높이 = 0.9 mm), 0.3 mm Pitch, 수평 결합, 백플립

Product Specifications:

Board Pitch (mm)	0.3
Wiping Length (mm)	Contact A:0.9
	Contact B:0.45
Size (mm)	Height 0.90 +/- 0.10
	Width Formula:1.5 + (0.3*?p)
	Depth Open:2.55 Close:3.5
Pin counts	Range 15-75 (odd)
	Available 51


Applicable FPC/FFC:

FPC/FFC Contact Pitch	0.3
FPC/FFC Contact Point	Top and Bottom
FPC/FFC Thickness (mm)	0.2 +/- 0.03




*기재가 되어있지 않은 핀 수의 대응 여부에 대해서는 문의해 부탁드립니다.

▶ 보강판에 의한 측벽 강도 강화



▶ 단자 변형 방지 설계




액추에이터를 열때 Contact가 위로 당겨지는 것을 Rib가 방지합니다

▶ FPC 미삽입 상태에서도 액추에이터 닫기 조작 가능(단자 변형 최소화)


SMT 공정 후에 FPC를 삽입하지 않고 우연히 액추에이터를 닫은 경우에도 Contact 변형 최소화

- 커넥터가 여전히 안정적으로 작동합니다(FPC를 삽입하지 않은 상태에서 액추에이터 작동 전후 접촉 간격 그래프 51핀)



- 커넥터의 삽입력 상승
- 커넥터의 고정력은 큰 변화 없음

Connector Assembly



PART NO.	Pos.	B	C	F	G
◆20982-015E-01	15P	3.60	4.20	4.80	5.65
◆20982-033E-01	33P	9.00	9.60	10.20	11.05
◆20982-035E-01	35P	9.60	10.20	10.80	11.65
◆20982-037E-01	37P	10.20	10.80	11.40	12.25
◆20982-039E-01	39P	10.80	11.40	12.00	12.85
◆20982-041E-01	41P	11.40	12.00	12.60	13.45
◆20982-045E-01	45P	12.60	13.20	13.80	14.65
◆20982-049E-01	49P	13.80	14.40	15.00	15.85
◆20982-051E-01	51P	14.40	15.00	15.60	16.45
◆20982-055E-01	55P	15.60	16.20	16.80	17.65
◆20982-057E-01	57P	16.20	16.80	17.40	18.25
◆20982-061E-01	61P	17.40	18.00	18.60	19.45
◆20982-065E-01	65P	18.60	19.20	19.80	20.65
◆20982-067E-01	67P	19.20	19.80	20.40	21.25
◆20982-071E-01	71P	20.40	21.00	21.60	22.45
◆20982-075E-01	75P	21.60	22.20	22.80	23.65

◆ MARK MEANS NOT AVAILABLE.

NOTES.


3. MATERIAL

- COVER FILM : PI
- CONDUCTOR : COPPER(RARE)
- BASE FILM : PI
- STIFFENER : PI
- ADHESIVE : THERMOSETTING ADHESIVE



4. FINISH

Au OVER Ni UNDER PLATING.


- SOLDER RESIST SHALL BE APPLIED TO PREVENT SHORT CIRCUITS WHEN PLACING SIGNAL LINES ON GROUND AREA.



RECOMMENDED PCB LAYOUT & METAL MASK LAYOUT
METAL MASK THICKNESS : t=0.12mm



CONNECTOR ON RECOMMENDED PCB LAYOUT



REFLOW TEMPERATURE PROFILE
SENJU METAL INDUSTRY CO., LTD. : M705-SHF(Sn96.5 Ag3.0 Cu0.5)

Rev.0

Rev.0

Connector Assembly

ITEMS	SPECIFICATION
RATING VOLTAGE	50V AC (PER CONTACT)
RATING AMPERAGE	0.3A DC (PER CONTACT)
OPERATING TEMPERATURE	233~358K (-40°C~+85°C)
OPERATING HUMIDITY	20~80%RH (NON-CONDENSING)
CONTACT RESISTANCE	INITIAL : 60mohm MAX. / AFTER TEST : \triangleleft 40mohm MAX.
INSULATION RESISTANCE	100Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	20 CYCLES
ACTUATOR LOCKING FORCE (INITIAL / 20 CYCLES)	INITIAL / 20 CYCLES 0.21N (21gf) \times n MAX.
ACTUATOR UNLOCKING FORCE (INITIAL / 20 CYCLES)	INITIAL / 20 CYCLES 0.014N (1.4gf) \times n MIN.
FPC RETENTION FORCE (INITIAL / AFTER TEST)	INITIAL: 0.13N (13gf) \times n MIN. / AFTER TEST: 0.10N (10gf) \times n MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2650
TEST REPORT	TR-20010
PACKING STANDARD	PST-15093
INSTRUCTION MANUAL	HIM-12007
APPEARANCE CRITERIA No.	QLS-A***

※ "n" IS THE NUMBER OF PIN


Rev.0


Custom Connectors Available

 RF Connector

MHF® series



 CABLINE® series
Micro-coaxial/Twinax/
Discrete Wire Connector




 Optical Module

LIGHTPASS® series



NOVASTACK® series

 Board-to-Board Connector



 Power Connector/
Terminal

AP series


ISH® series



MINIFLEX® series

EVAFLEX® series

 FPC FFC Connector




Inquiry



MINIDOCK® series

 I/O Connector



I-PEX, MHF, CABLINE, LIGHTPASS, NOVASTACK, ISH, IARPB, MINIFLEX, EVAFLEX, MINIDOCKS and ZenShield are registered trademarks of I-PEX Inc. Please note that the contents in the catalog might be changed without prior notification. I-PEX Inc. assumes no responsibility for any inaccuracies or obligation to update information on these documents. Please be sure to read and understand the latest "Precautions for Use" and "Instruction Manual" before you use our products. We shall not be responsible for any defects, damages or troubles in case you use our products without following the precautions for use. Please feel free to contact our sales representatives when you use our products for any applications that require very high reliability and safety, or that relate to human life (ex. nuclear power control, aerospace, transportation, medical equipment, safety equipment etc.).

Contact your sales representative or more detailed information.

www.i-pex.com



I-PEX

© I-PEX Inc. 2024
All rights reserved