

PART NO.	Pos.
20790-060E-##	60

P/N : 20790-0 ** E- ##

- 1 : WITH BOSS
2 : WITHOUT BOSS

SEE TABLE 1

Pos.
135° MAX.









TABLE 1

PART NO.	CONTACT FINISH
20790-0**E-0#	CONTACT & SOLDERING AREA : Au 0.03 μ m MIN. OVER Ni 1.00 μ m MIN.
20790-0**E-1#	CONTACT AREA : Au 0.38 μ m MIN. OVER Ni 1.00 μ m MIN. SOLDERING AREA : Au 0.03 μ m MIN. OVER Ni 1.00 μ m MIN.


NO.	DISCRIPTION	MATERIAL	FINISH , REMARKS
3	SHELL	PHOSPHOR BRONZE	ALL OVER Ni 1.00 μ m MIN. SOLDERING AREA : Au 0.03 μ m MIN.
2	CONTACT	PHOSPHOR BRONZE	SEE TABLE 1
1	HOUSING	LCP	UL94V-0 ,BLACK

18	Z250838	K.W	2025/06/09	M.T	ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION	SERIES No.	CUSTOMER COPY		
17	Z250426	K.Hara	2025/03/13	H.I	6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R0			
16	Z250091	K.Hara	2025/01/24	H.I	GENERAL TOLERANCE.				TITLE		SCALE	I-PEX	
15	Z241786	K.Hara	2024/12/13	H.I	DWG.	DATE			CABLINE® -CA II PLUS RECEPTACLE ASSEMBLY		5:1		
14	Z241307	K.Hara	2024/09/24	H.I	T.Masunaga			2016/11/14			UNIT		
13	Z240025	K.Hara	2024/01/12	H.I	T.Kurachi			CHK.			mm		
REV.	ECN	BY	DATE	APP.	APP.				DWG. No.		SIZE	SHEET	REV.
REVISION RECORD					J.Tateishi			20790		A3	1/6	18	

PATENT REGISTERED


FOR CABLINE-CA II PLUS PLUG CABLE ASSEMBLY (DWG. NO. 20788)


ITEMS	SPECIFICATION
APPLICABLE CABLE	MICRO-COAXIAL CABLE : AWG #44 , 42 , 40 , 38 , 36 DISCRETE WIRE : AWG #36 , 34 TWINAXIAL CABLE : AWG #40 , 42
RATED VOLTAGE	100V AC (PER CONTACT PIN) ※THIS IS THE RATED VOLTAGE OF THE CONNECTOR. PLEASE NOTE THAT THE RATED VOLTAGE MAY VARY IN THE HARNESS DEPENDING ON THE CABLES USED.
RATED AMPERAGE (FOR CONTACT)	0.1A AC/DC [AWG #44] PER CONTACT PIN/UP TO 60 CONTACTS 0.24A AC/DC [AWG #42] PER CONTACT PIN/UP TO 60 CONTACTS 0.3A AC/DC [AWG #40] PER CONTACT PIN/UP TO 60 CONTACTS 0.5A AC/DC [AWG #38] PER CONTACT PIN/UP TO 18 CONTACTS 0.8A AC/DC [AWG #36] PER CONTACT PIN/UP TO 6 CONTACTS 1.0A AC/DC [AWG #34] PER CONTACT PIN/UP TO 6 CONTACTS ※TESTING BY REAL MACHINE IS RECOMMENDED BECAUSE TEMPERATURE RISE MAY AFFECTED BY ACTUAL SITUATION.
OPERATING TEMPERATURE	233 TO 378K (−40°C TO 105°C)
OPERATING HUMIDITY	85% MAX
CONTACT RESISTANCE	INITIAL : 180mohm MAX.(AWG #34) / AFTER TEST : $\triangle$ 40mohm MAX. 275mohm MAX.(AWG #36) 360mohm MAX.(AWG #38) 600mohm MAX.(AWG #40) 700mohm MAX.(AWG #42) 1080mohm MAX.(AWG #44)
GROUND SHELL RESISTANCE	INITIAL : 50mohm MAX. / AFTER TEST : $\triangle$ 40mohm MAX.
INSULATION RESISTANCE	INITIAL : 1000Mohm MIN. / AFTER TEST : 500Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	30 CYCLES
MATING FORCE (INITIAL / AFTER 30 CYCLES)	29.10N MAX.
UN-MATING FORCE (INITIAL / AFTER 30 CYCLES)	6.0N MIN.
CABLE RETENTION FORCE	29.40N MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2261
TEST REPORT	TR-16075, TR-23031
INSTRUCTION MANUAL	HIM-16028
PACKING STANDARD	PST-16078
APPEARANCE CRITERIA NO.	QLS-A***

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R0	CUSTOMER COPY					
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5								
GENERAL TOLERANCE.				TITLE CABLINE®-CA II PLUS RECEPTACLE ASSEMBLY		SCALE	I-PEX				
DWG.	DATE					-					
CHK.						UNIT					
APP.						mm					
				DWG. No.		SIZE	SHEET	REV.			
				20790		A3	2/6	18			


FOR CABLINE-CA IIF PLUS PLUG SHELL ASSEMBLY (DWG. NO. 20901)

ITEMS	SPECIFICATION
RATED VOLTAGE	100V AC (PER CONTACT PIN)
RATED AMPERAGE (FOR SIGNAL CONTACT)	0.3A AC/DC (PER CONTACT PIN) ※TESTING BY REAL MACHINE IS RECOMMENDED BECAUSE TEMPERATURE RISE MAY AFFECTED BY ACTUAL SITUATION.
OPERATING TEMPERATURE	233 TO 358K (−40℃ TO +85℃)
OPERATING HUMIDITY	85% MAX.
CONTACT RESISTANCE (FOR SIGNAL CONTACT)	INITIAL : 60mohm MAX. / AFTER TEST : $\triangleleft$ 40mohm MAX.
GROUND SHELL RESISTANCE	INITIAL : 60mohm MAX. / AFTER TEST : $\triangleleft$ 40mohm MAX.
INSULATION RESISTANCE	INITIAL : 1000Mohm MIN. / AFTER TEST : 500Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	30 CYCLES
MATING FORCE (INITIAL / AFTER TEST)	27.0N MAX.
UNMATING FORCE (INITIAL / AFTER TEST)	2.88N MIN.
PRODUCT SPECIFICATION	PRS-2893
TEST REPORT	TR-24034
PACKING STANDARD	PST-24023
INSTRUCTION MANUAL	HIM-24010
ASSEMBLY MANUAL	ASM-24004
APPEARANCE CRITERIA No.	QLS-A***

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R0	CUSTOMER COPY				
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5							
GENERAL TOLERANCE.				TITLE CABLINE®-CA II PLUS RECEPTACLE ASSEMBLY		SCALE	I-PEX			
DWG.	DATE					—				
CHK.						UNIT				
APP.						mm				
				DWG. No. 20790		SIZE A3	SHEET 3/6	REV. 18		





RECOMMENDED FOOTPRINT PATTERN LAYOUT



RECOMMENDED METAL MASK LAYOUT
METAL MASK THICKNESS : t=0.12mm

- NOTES.
- DO NOT MOUNT ANOTHER COMPONENT IN THIS AREA.
 - SOLDER RESIST MUST BE APPLIED TO THIS AREA.


ANGLE	±2°	6 OVER 30 MAX.	±0.3		SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R0			
GENERAL TOLERANCE.				TITLE	SCALE			
DWG.		DATE		CABLINE®-CA II PLUS RECEPTACLE ASSEMBLY		5:1		
CHK.						UNIT		
						mm		
APP.				DWG. No.	SIZE		SHEET	REV.
				20790	A3		4/6	18



SENJU METAL INDUSTRY CO., LTD. : M705-SHF(Sn96.5 Ag3.0 Cu0.5)

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION	SERIES No. R0	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
GENERAL TOLERANCE.				TITLE CABLINÉ® –CA II PLUS RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.		DATE				5:1		
CHK.						UNIT		
						mm		
APP.				DWG. No. 20790		SIZE A3	SHEET 5/6	REV. 18

PART NO.	QTY. PER EMBOSS REEL (PIECES / REEL)	QTY. PER PACKING CARTON (REELS / CARTON)
20790-060E-##	5500 / REEL	3 / CARTON = 16500



- NOTES.
3. TAPING SPECIFICATION FOLLOWS JIS C 0806 (IEC 60286-3).
 4. EMPTY SECTION OF LEADER AND END ON EACH END OF THE TAPE FOLLOW JIS C 0806 (IEC 60286-3).
 5. TOP TAPE SHALL NOT STICK OUT FROM EMBOSS TAPE.
 6. TOP TAPE SHALL NOT COVER FEED HOLE.

7	PACKING LABEL	-	-
6	REEL	PS	ANTI-STATIC TYPE BLACK
5	TOP TAPE	PET TRANSPARENCY	ANTI-STATIC TYPE
4	EMBOSS TAPE	PS TRANSPARENCY	ANTI-STATIC TYPE
NO.	DISCRIPTION	MATERIAL	FINISH , REMARKS

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION	SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R0			
GENERAL TOLERANCE.				TITLE		SCALE		
DWG.	DATE			CABLINC®-CA II PLUS RECEPTACLE ASSEMBLY		2:1		
CHK.						UNIT		
						mm		
APP.				DWG. No.		SIZE	SHEET	REV.
				20790		A3	6/6	18