


Recommended P/N 20849-0**E-01

PART NO.	Pos.	A	B	C	D	E
20849-020E-0#	20	11.30	9.50	14.33	15.10	11.91
20849-030E-0#	30	16.30	14.50	19.33	20.10	16.91
20849-040E-0#	40	21.30	19.50	24.33	25.10	21.91



P/N : 20849- 0 ** E- 0 #
SEE TABLE 1
POS.







Halogen Free




RoHS Compliant




BOTTOM VIEW



SECT. W-W
(S = 10 : 1)



MATING CONDITION
(S = 10 : 1)



PLUG P/N : 20846-0**T-0#

MATING CONDITION

TABLE.1

PART NO.	CONTACT FINISH	SHELL FINISH
20849-0**E-01	CONTACT & SOLDERING AREA : Au 0.03 μ m MIN. OVER Ni 1.00 μ m MIN.	ALL OVER Ni 1.00 μ m MIN. SOLDERING AREA : Au 0.02 μ m MIN.
20849-0**E-02	CONTACT AREA : Au 0.38 μ m MIN. OVER Ni 1.27 μ m MIN. SOLDERING AREA : Au 0.03 μ m MIN. OVER Ni 1.00 μ m MIN.	

3	SHELL	PHOSPHOR BRONZE	SEE TABLE 1
2	CONTACT	PHOSPHOR BRONZE	SEE TABLE 1
1	HOUSING	LCP	UL94V-0, BLACK
NO.	DISCRIPTION	MATERIAL	FINISH , REMARKS




16	ZC00276	K.Ta	2025/11/21	T.M	ANGLE	±2°	6 OVER 30 MAX.	±0.3		SERIES No. R2	CUSTOMER COPY		
15	Z250980	K.W	2025/06/18	M.T	6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
14	Z250308	K.Ta	2025/02/27	T.M	GENERAL TOLERANCE.				TITLE CABLINE® –VS II RECEPTACLE ASSEMBLY	SCALE 5:1 UNIT mm			
13	Z241820	T.Ono	2024/12/18	T.M	DWG.	DATE							
12	Z241779	T.Ono	2024/12/12	T.M	K.Baba 2017/07/25								
11	Z240932	K.hara	2024/07/16	H.I	CHK.								
REV.	ECN	BY	DATE	APP.	T.Kurachi				DWG. No.	20849	SIZE A3	SHEET 1/9	REV. 16
REVISION RECORD					Y.Shimada								

PATENT REGISTERED

PART NO.	Pos.
20849-020E-0#	20
20849-030E-0#	30
20849-040E-0#	40

BOTTOM VIEW

PATENT REGISTERED



ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R2	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
GENERAL TOLERANCE.				TITLE CABLINE® –VS II RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.	DATE					5:1		
CHK.						UNIT		
APP.						mm		
				DWG. No. 20849		SIZE	SHEET	REV.
						A3	2/9	16

FOR CABLINE-VS II PLUG CABLE ASSEMBLY (DWG NO. 20846)

ITEMS	SPECIFICATION
APPLICABLE CABLE	MICRO-COAXIAL CABLE : AWG #44 , 42 , 40 , 38 , 36 DISCRETE WIRE : AWG #36 , 34 , 32 TWINAXIAL CABLE : AWG #40
RATED VOLTAGE	100V AC (PER CONTACT PIN) ※THIS IS THE RATED VOLTAGE OF THE CONNECTOR. PLEASE NOTE THAT THE RATED VOLTAGE MAY VARY IN THE HARNESS DEPENDING ON THE CABLES USED.
RATED AMPERAGE (FOR CONTACT)	0.1A AC/DC [AWG #44] PER CONTACT PIN/UP TO 40 CONTACTS 0.24A AC/DC [AWG #42] PER CONTACT PIN/UP TO 40 CONTACTS 0.3A AC/DC [AWG #40] PER CONTACT PIN/UP TO 40 CONTACTS 0.5A AC/DC [AWG #38] PER CONTACT PIN/UP TO 23 CONTACTS 0.8A AC/DC [AWG #36] PER CONTACT PIN/UP TO 10 CONTACTS 1.0A AC/DC [AWG #34] FOR POWER PER CONTACT PIN/UP TO 9 CONTACTS 1.0A AC/DC [AWG #32] FOR POWER PER CONTACT PIN/UP TO 9 CONTACTS ※TESTING BY A REAL MACHINE IS RECOMMENDED BECAUSE TEMPERATURE RISE MAY AFFECTED BY ACTUAL SITUATION.
OPERATING TEMPERATURE	233 TO 378K (−40℃ TO +105℃)
OPERATING HUMIDITY	85% MAX.
CONTACT RESISTANCE	INITIAL : 140mohm MAX.(AWG #32) / AFTER TEST : $\triangle$ 40mohm MAX. 180mohm MAX.(AWG #34) 275mohm MAX.(AWG #36) 360mohm MAX.(AWG #38) 600mohm MAX.(AWG #40) 700mohm MAX.(AWG #42) 1080mohm MAX.(AWG #44)
GROUND SHELL RESISTANCE	INITIAL : 50mohm MAX. / AFTER TEST : $\triangle$ 40mohm MAX.
INSULATION RESISTANCE	INITIAL : 1000Mohm MIN. / AFTER TEST : 500Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	30 CYCLES
MATING FORCE (INITIAL / AFTER 30 CYCLES)	20P : 9.70N MAX. / 30P : 14.55N MAX. / 40P : 19.40N MAX.
UNMATING FORCE (INITIAL / AFTER 30 CYCLES)	20P : 2.00N MIN. / 30P : 3.00N MIN. / 40P : 4.00N MIN.
CABLE RETENTION FORCE	20P : 9.80N MIN. / 30P : 14.70N MIN. / 40P : 19.60N MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2398
TEST REPORT	TR-17060 (20849-0**E-01) / TR-18048 (20849-0**E-02)
PACKING STANDARD	PST-17079
INSTRUCTION MANUAL	HIM-17015
ASSEMBLY MANUAL	ASM-17005
APPEARANCE CRITERIA No.	QLS-A***




ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R2	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
GENERAL TOLERANCE.				TITLE CABLINE®-VS II RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.	DATE					—		
CHK.						UNIT		
APP.						mm		
				DWG. No. 20849		SIZE A3	SHEET 3/9	REV. 16

FOR CABLINE-VS IIF PLUG SHELL ASSEMBLY (DWG NO. 20862)

ITEMS	SPECIFICATION
RATED VOLTAGE	100V AC (PER CONTACT PIN)
RATED AMPERAGE (FOR CONTACT)	0.3A AC/DC (PER CONTACT PIN) ※TESTING BY A REAL MACHINE IS RECOMMENDED BECAUSE TEMPERATURE RISE MAY AFFECTED BY ACTUAL SITUATION.
OPERATING TEMPERATURE	233 TO 358K (-40℃ TO +85℃)
OPERATING HUMIDITY	85% MAX.
CONTACT RESISTANCE (FOR SIGNAL CONTACT)	INITIAL : 60mohm MAX. / AFTER TEST : $\triangle$ 40mohm MAX.
GROUND SHELL RESISTANCE	INITIAL : 60mohm MAX. / AFTER TEST : $\triangle$ 40mohm MAX.
INSULATION RESISTANCE	INITIAL : 1000Mohm MIN. / AFTER TEST : 500Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	30 CYCLES
MATING FORCE (INITIAL / AFTER TEST)	30P : 13.50N MAX. 40P : 18.00N MAX.
UNMATING FORCE (INITIAL / AFTER TEST)	30P : 1.44N MIN. 40P : 1.92N MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2430
TEST REPORT	TR-17086
PACKING STANDARD	PST-17079
INSTRUCTION MANUAL	HIM-17039
APPEARANCE CRITERIA NO.	QLS-A***

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R2	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
GENERAL TOLERANCE.				TITLE CABLINE®-VS II RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.	DATE					-		
CHK.						UNIT		
APP.						mm		
				DWG. No. 20849		SIZE A3	SHEET 4/9	REV. 16


PATENT REGISTERED




- NOTES.
1. SOLDER RESIST MUST BE APPLIED TO THIS AREA.
 2. DO NOT MOUNT ANOTHER COMPONENT IN THIS AREA.

ANGLE	±2°	6 OVER 30 MAX.	±0.3		SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R2			
GENERAL TOLERANCE.				TITLE CABLIN® –VS II RECEPTACLE ASSEMBLY		SCALE		
DWG.	DATE					5:1		
CHK.						UNIT		
APP.						mm		
				DWG. No.	SIZE	SHEET	REV.	
				20849	A3	5/9	16	


PATENT REGISTERED



30P RECOMMENDED FOOTPRINT PATTERN LAYOUT



30P RECOMMENDED METAL MASK LAYOUT
METAL MASK THICKNESS : t=0.12mm




DETAIL AA
(S = 10 : 1)


- NOTES.
- 1. SOLDER RESIST MUST BE APPLIED TO THIS AREA.
 - 2. DO NOT MOUNT ANOTHER COMPONENT IN THIS AREA.

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION	SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R2			
GENERAL TOLERANCE.				TITLE CABLIN [®] –VS II RECEPTACLE ASSEMBLY		SCALE		
DWG.	DATE					5:1		
CHK.				UNIT				
APP.				mm				
				DWG. No.	20849	SIZE	SHEET	REV.
						A3	6/9	16


PATENT REGISTERED



40P RECOMMENDED FOOTPRINT PATTERN LAYOUT




DETAIL AA
(S = 10 : 1)




40P RECOMMENDED METAL MASK LAYOUT
METAL MASK THICKNESS : t=0.12mm

- NOTES.
- 1. SOLDER RESIST MUST BE APPLIED TO THIS AREA.
 - 2. DO NOT MOUNT ANOTHER COMPONENT IN THIS AREA.


ANGLE	±2°	6 OVER 30 MAX.	±0.3		SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R2			
GENERAL TOLERANCE.				TITLE CABLIN [®] -VS II RECEPTACLE ASSEMBLY		SCALE		
DWG.	DATE					5:1		
CHK.						UNIT		
APP.						mm		
				DWG. No.	SIZE	SHEET	REV.	
				20849	A3	7/9	16	




CONNECTOR ON RECOMMENDED FOOTPRINT PATTERN



REFLOW TEMPERATURE PROFILE
SENJU METAL INDUSTRY CO., LTD. : M705-SHF(Sn96.5 Ag3.0 Cu0.5)

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. R2	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5					
GENERAL TOLERANCE.				TITLE CABLIN [®] -VS II RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.	DATE					5:1		
CHK.						UNIT		
						mm		
APP.				DWG. No.	20849	SIZE	SHEET	REV.
					A3	8/9	16	

PART NO.	M	N	P	R	QTY. PER EMBOSS REEL (PIECES / REEL)	QTY. PER PACKING CARTON (REELS / CARTON)
20849-020E-0#	24.00	11.50	-	15.50	8000 / REEL	5 / CARTON = 40000
20849-030E-0#	32.00	14.20	28.40	20.50		4 / CARTON = 32000
20849-040E-0#	44.00	20.20	40.40	25.50		3 / CARTON = 24000



- NOTES.
- TAPING SPECIFICATION FOLLOWS JIS C 0806 (IEC 60286-3).
 - EMPTY SECTION OF LEADER AND END ON EACH END OF THE TAPE FOLLOW JIS C 0806 (IEC 60286-3).
 - TOP TAPE SHALL NOT STICK OUT FROM EMBOSS TAPE.
 - TOP TAPE SHALL NOT COVER FEED HOLE.

7	PACKING LABEL	-	-
6	REEL	PS	ANTI-STATIC TYPE BLACK
5	TOP TAPE	PET TRANSPARENCY	ANTI-STATIC TYPE
4	EMBOSS TAPE	PS TRANSPARENCY	ANTI-STATIC TYPE
NO.	DISCRIPTION	MATERIAL	FINISH , REMARKS

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION	SERIES No.	CUSTOMER COPY		
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5		R2			
GENERAL TOLERANCE.				TITLE CABLIN®-VS II RECEPTACLE ASSEMBLY		SCALE	I-PEX	
DWG.	DATE					UNIT		
CHK.						mm		
APP.						SIZE		
				DWG. No.	20849	SIZE	SHEET	REV.
						A3	9/9	16