



- NOTE.
1. TO HANDLE THIS CONNECTOR YOU MUST READ AND FOLLOW THE INSTRUCTION MANUAL BELOW. I-PEX INSTRUCTION MANUAL No.HIM-16028.
 2. ELECTRIC CHARACTERISTICS
WITHSTANDVOLTAGE : AC 250V LEAKAGE CURRENT 2.0mA MAX.
INSULATION RESISTANCE : 50MΩ MIN. DC 100V
 3. THE OPERATING TEMPERATURE OF THE HARNESS : 80°C MAX.
 4. RATING VOLTAGE : 30V

PIN ASSIGNMENT		
CONNECTOR 1	CABLE	CONNECTOR 2
60	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	60
.	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	.
1	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	1

NO.	DESCRIPTION	PARTS NO.	QTY	REMARK
6	ACETATE TAPE	-	3	BLACK
5	BONDING	-	-	UV GLUE
4	CABLE	-	60	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE
3	LOCK BAR ASSEMBLY	20789-060T-01	2	CONNECTOR 1 & 2 CABLINE-CA II PLUS PLUG P/N : 20788-060T-01 CONNECTOR TO BE MATED : 20790-060E-02
2	SHELL-A	3204-0601	2	
1	HOUSING ASSEMBLY	20680-060T-01	2	

REVISION RECORD				GENERAL TOLERANCE.		PROJECTION		SERIES No.		CUSTOMER COPY	
0	ZM00910	K.Fu	2026/05/28	-	ANGLE	±2°	6 OVER 30 MAX.	±0.3	IH-200016	TITLE	SCALE
REV.	ECN	BY	DATE	APP.	6 MAX.	±0.2	30 OVER 120 MAX.	±0.5			
					DWG. K.Fukutomi		DATE	2026/05/28	DWG. No.	SIZE	SHEET
					CHK. R.Takei						
					APP. T.Masunaga						REV.
											0

Confidential C

I-PEX Inc.

QKE-DFE06-02 REV.12