PART No.
82436-100B-02-D



CONNECTOR 1&2 (S=5/1)





DETAIL X
(S=5/1)

PIN ASSIGNMENT		
CONNECTOR 1	CABLE	CONNECTOR 2
50	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	1
49	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	2
▪ ▪ ▪	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	▪ ▪ ▪
2	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	49
1	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE	50

NOTE.
1. TO HANDLE THIS CONNECTOR
   YOU MUST READ AND FOLLOW THE INSTRUCTION MANUAL BELOW.
   I-PEX INSTRUCTION MANUAL No.HIM-15033.
2. ELECTRIC CHARACTERICTICS
   WITHSTANDVOLTAGE : AC 250V LEAKAGE CURRENT 2.0mA MAX.
   INSULATION RESISTANCE : 50MΩ MIN. DC 100V
3. THE OPERATING TEMPERATURE OF THE HARNESS : 80℃ MAX.
4. RATING VOLTAGE : 30V

NO.	DESCRIPTION	PARTS NO.	QTY	REMARK
6	ACETATE TAPE	–	3	BLACK
5	BONDING	–	–	UV GLUE
4	CABLE	–	50	MICRO-COAXIAL CABLE AWG#40 50 OHM, BLUE
3	LOCK BAR ASSEMBLY	20681-050T-01	2	CONNECTOR 1&2
2	SHELL-A	3204-0501	2	CABLINE-CA II PLUG P/N : 20679-050T-01
1	HOUSING ASSEMBLY	20680-050T-01	2	CONNECTOR TO BE MATED : 20682-050E-02

REV.	ECN	BY	DATE	APP.
1	ZM01103	K.B	2026/07/23	T.M
0	Z250808	K.B	2025/05/22	–

REVISION RECORD

ANGLE	±2°	6 OVER 30 MAX.	±0.3	
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5	

GENERAL TOLERANCE.

PROJECTION

SERIES No. IH-200016

CUSTOMER COPY

DWG. K.Baba DATE 2025/05/22

CHK. R.Takei

APP. H.Ikari

TITLE: CABLINE®-CA II 50P HARNESS

DWG. No. 82436

SCALE 2:1

UNIT mm

SIZE A3

SHEET 1/1

REV. 1

I-PEX