

ITEMS	SPECIFICATION			
APPLICABLE CONNECTOR PART No.	20549-001E-**			
RATING FREQUENCY	DC~11GHz			
OPERATING TEMPERATURE	233~343K(-40°C~+70°C)			
VSWR	1.4 MAX. (DC~3GHz), 1.8 MAX. (3GHz~6GHz), 2.2 MAX. (6GHz~11Hz)			
DIELECTRIC WITHSTANDING VOLTAGE	AC100V 1min			
DURABILITY	1,000 CYCLES			
PRODUCT SPECIFICATION	PRS-1759			
TEST REPORT	TR-12131			
INSTRUCTION MANUAL	HIM-13004			
APPEARANCE CRITERIA No.	QLS-A***			

ANGLE $\pm 2^{\circ}$ 6 OVER 30 MAX. ± 0.3	PROJECTION SERIES No.		CUSTOMER COPY		
6 MAX. ±0.2 30 OVER 120 MAX. ±0.5	$\Theta \subseteq$	R0	COSTOMER COPT		
GENERAL TOLERANCE.	TITLE		SCALE		
DWG. DATE	MHF® -SW23	I-PEX			
CHK.	SMA ADAPTER CABLE				
CHK.			/		
APP.	DWG. No. 90582		SIZE	SHEET	REV.
			A3	2/2	5