

ITEMS	SPECIFICATION
RECOMMENDED APPLICABLE CONNECTOR PART No.	MHF 4 SIDE : MHF4 RECEPTACLE(P/N : 20449-001E-**, 20579-001E-**) BASE UNIT SIDE : MHF SERIES HIGH CYCLE SMA ADAPTER BASE UNIT (P/N : 90684-0001)
RATING FREQUENCY	DC~6 GHz
OPERATING TEMPERATURE	233~358 K (-30°C~+70°C)
VSWR	1.2 MAX. (DC~6GHz)
INSULATION RESISTANCE	500 Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC 300V 1min
DURABILITY	10,000CYCLES
PRODUCT SPECIFICATION	-
TEST REPORT	-
INSTRUCTION MANUAL	HIM-14021

ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION 	SERIES No. -	CUSTOMER COPY
6 MAX.	±0.2	30 OVER 120 MAX.	±0.5			
GENERAL TOLERANCE.				TITLE MHF® 4 RECEPTACLE HIGH CYCLE ATTACHMENT	SCALE -	UNIT mm
DWG.	DATE					
CHK.	DATE					
APP.	DATE					
				DWG. No.	90683	SIZE A3
				SHEET 2/2		REV. 1