





PART NO.	L
8-25-0867	400.00±3.0 mm


PLEASE CONTACT I-PEX FOR REQUESTS OTHER THAN THIS SPECIFICATIONS.
PLEASE NOTE IF SPECIFICATIONS CHANGE, PART NO. WILL ALSO CHANGE.

- NOTES
1. PACKING : PLASTIC BAG
 2. PERMISSIBLE LOAD ON THE CABLE AFTER MATING
 3. CABLE CRIMP STRENGTH : 10N MIN.
 4. TO OPERATE LOCK PART
FOLLOW I-PEX INSTRUCTION MANUAL HIM-17020.
 5. DO NOT ROTATE THE PLUG IN THE MATING CONDITION.




MULTIPLE CONNECTORS LAYOUT

COMPONENTS PLACEMENT PROHIBITED AREA
REQUIRED AREA FOR RECOMMENDED JIG TO OPERATE
MHF I LK HARNESS IN 4.50±0.15 mm PITCH (M.2 PITCH) SMOOTHLY.
JIG PART NUMBER: 91492-0001




SINGLE CONNECTOR LAYOUT


COMPONENTS PLACEMENT PROHIBITED AREA
FOR PLUG 360° ROTATION AND UNMATING AND LOCK
JIG PART NUMBER: 91026-0001, 91492-0001



Φ 9.50 MIN.
THE CENTER OF THE CIRCLE MATCHES
THE CENTER OF RECEPTACLE.



UNLOCKED CONDITION



LOCKED CONDITION

DO NOT MATE WITH RECEPTACLE
UNDER THIS LOCKED CONDITION.

**MATING AND LOCK CONDITION
WITH MHF I LK HARNESS**

**MATING AND LOCK CONDITION
WITH MHF I LK HARNESS NARROW PITCH**

**MHF I LK HARNESS UNLOCK CONDITION
NARROW PITCH DIMENSIONS**

3	LOCK PART	2	-
2	CABLE	1	AWG#32 Φ 1.13, BRAIDED SHIELD , BLACK
1	CONNECTOR-1, 2	2	MHF I Au
NO.	DESCRIPTION	QTY	REMARK

				ANGLE	±2°	6 OVER 30 MAX.	±0.3	PROJECTION ⊕	SERIES No. H-250066D	CUSTOMER COPY					
					6 MAX.	±0.2	30 OVER 120 MAX.				±0.5				
				GENERAL TOLERANCE.				TITLE MHF® I-I CABLE113-2 +LK	SCALE X:1	UNIT mm	I-PEX				
				DWG.	M.Toida		DATE					2026/01/27			
				CHK.	T.Takuno										
0	ZH00373	TOI	2026/01/27	APP.	K.Yufu			DWG. No.	8-25-0867	SIZE	A3	SHEET	1/1	REV.	0

REVISION RECORD



Confidential C

I-PEX Inc.

QKE-DFE06-02 REV.12