




PART NO.	L
8-25-0837	100.00±1.0 mm


PLEASE CONTACT I-PEX FOR REQUESTS OTHER THAN THIS SPECIFICATIONS.
PLEASE NOTE IF SPECIFICATIONS CHANGE, PART NO. WILL ALSO CHANGE.




- NOTES
1. SUGGESTIONS FOR MATING & UNMATING OPERATION.
- 1-1. MATING
MATE THE CONNECTOR VERTICALLY,
ALIGNING THE MATING AXIS ON PLUG AND RECEPTACLE.
DO NOT SLANT MATE.
- 1-2. UNMATING
- 1-2-1.
UNMATING BY PULLING TOOL.
[P/N 90192-001 (MHF I),]
USE THE PULLING TOOL AS THE FOLLOWING, AND
PULL PLUG TO VERTICAL DIRECTION AS DIRECTLY AS POSSIBLE.



- 1-2-2.
UNMATING DIRECTLY BY HAND.
HOLD THE CATCHING AREA ON PLUG AND PULL THE PLUG
VERTICALLY.



2. PACKING : PLASTIC BAG
3. PERMISSIBLE LOAD ON THE CABLE AFTER MATING



4. CABLE CRIMP STRENGTH : 10N MIN.

2	CABLE	1	AWG#32 Φ 1.32, BRAIDED SHIELD , BLACK
1	CONNECTOR-1, 2	2	MHF I Au
NO.	DESCRIPTION	QTY	REMARK

					ANGLE	±2°	6 OVER 30 MAX.	±0.3		SERIES No.	H-250059A	CUSTOMER COPY		
					6 MAX.	±0.2	30 OVER 120 MAX.	±0.5						
					GENERAL TOLERANCE.				TITLE MHF® I-I CABLE132-2		SCALE	I-PEX		
					DWG.	DATE					X:1			
					M.Toida 2025/12/04						UNIT			
					CHK. T.Takuno						mm			
0	ZH00201	TOI	2025/12/04	-	APP.				DWG. No.	8-25-0837		SIZE	SHEET	REV.
REVISION RECORD					K.Yufu						A3	1/1		0



Halogen Free



RoHS Compliant

Confidential C

I-PEX Inc.

QKE-DFFDE06-02 REV.12