

MINIFLEX® 3-BFN L-HD

Robust design with hold-down feature, long actuator, low profile (Height = 0.9 mm), 0.3 mm pitch, horizontal, backflip

Product Specifications:

Board Pitch (mm)		0.3
Wiping Length (mm)		Contact A:0.9
		Contact B:0.45
Size (mm)	Height	0.90 +/- 0.10
	Width	Formula:1.5 + (0.3*?p)
	Depth	Open:2.55
		Close:3.5
Pin counts	Range	15-75 (odd)
	Available	51


Applicable FPC/FFC:

FPC/FFC Contact Pitch	0.3
FPC/FFC Contact Point	Top and Bottom
FPC/FFC Thickness (mm)	0.2 +/- 0.03


* Please inquire for pin counts not listed or outside of the pin count range.



► Hold-down feature improves strength of side wall



► Designed to prevent contact distortion




When opening the actuator, the rib will prevent the contacts from being pulled up

► Usability for closing actuator without FPC

The connector will still function even if the actuator is accidentally closed without the FPC being inserted after the SMT process.

- Connector will still function reliably (contact gap graph 51 pins before and after operating actuator without FPC inserted).




- Insertion force of connector goes up
- Retention force of connector does not change greatly

Connector Assembly

TABLE 1			
PART NO.		FINISH	
20982-0**E-01		CONTACT AREA : Au 0.10 μ m MIN. OVER Ni 1.00 μ m MIN. SOLDERING AREA : Au 0.03 μ m MIN. OVER Ni 1.00 μ m MIN.	
5	HOLD DOWN	PHOSPHOR BRONZE	Sn 2~6 μ m MIN. OVER Ni 1.00 μ m MIN.
4	CONTACT (B)	PHOSPHOR BRONZE	SEE TABLE 1, WITH Ni STRIPE
3	CONTACT (A)	PHOSPHOR BRONZE	SEE TABLE 1
2	ACTUATOR	LCP	UL94V-0, BEIGE
1	HOUSING	LCP	UL94V-0, BEIGE
NO.	DISCRPTION	MATERIAL	FINISH . REMARKS

Connector Assembly



PART NO.	Pos.	B	C	F	G
◆20982-015E-01	15P	3.60	4.20	4.80	5.65
◆20982-033E-01	33P	9.00	9.60	10.20	11.05
◆20982-035E-01	35P	9.60	10.20	10.80	11.65
◆20982-037E-01	37P	10.20	10.80	11.40	12.25
◆20982-039E-01	39P	10.80	11.40	12.00	12.85
◆20982-041E-01	41P	11.40	12.00	12.60	13.45
◆20982-045E-01	45P	12.60	13.20	13.80	14.65
◆20982-049E-01	49P	13.80	14.40	15.00	15.85
20982-051E-01	51P	14.40	15.00	15.60	16.45
◆20982-055E-01	55P	15.60	16.20	16.80	17.65
◆20982-057E-01	57P	16.20	16.80	17.40	18.25
◆20982-061E-01	61P	17.40	18.00	18.60	19.45
◆20982-065E-01	65P	18.60	19.20	19.80	20.65
◆20982-067E-01	67P	19.20	19.80	20.40	21.25
◆20982-071E-01	71P	20.40	21.00	21.60	22.45
◆20982-075E-01	75P	21.60	22.20	22.80	23.65

◆ MARK MEANS NOT AVAILABLE.

NOTES.

3. MATERIAL

COVER FILM : P1

CONDUCTOR : COPPER(RARE)
BASE FILM : PI

BASE FILM
STIFFNESS


STIFFENER : PI
ADHESIVE : THERMOSETTING ADHESIVE

4. FINISH


4. FINISH

AU OVER Ni UNDER PLATING.


5. SOLDER RESIST SHALL BE APPLIED TO PREVENT SHORT CIRCUITS WHEN PLACING SIGNAL LINES ON GROUND AREA.




RECOMMENDED PCB LAYOUT & METAL MASK LAYOUT
METAL MASK THICKNESS : $t=0.12\text{mm}$



Rev.0



CONNECTOR ON RECOMMENDED PCB LAYOUT



REFLOW TEMPERATURE PROFILE
SENJU METAL INDUSTRY CO., LTD. : M705-SHF(Sn96.5 Ag3.0 Cu0.5)

Connector Assembly

ITEMS	SPECIFICATION
RATING VOLTAGE	50V AC (PER CONTACT)
RATING AMPERAGE	0.3A DC (PER CONTACT)
OPERATING TEMPERATURE	233~358K (-40°C~+85°C)
OPERATING HUMIDITY	20~80%RH (NON-CONDENSING)
CONTACT RESISTANCE	INITIAL : 60mohm MAX. / AFTER TEST : \triangle 40mohm MAX.
INSULATION RESISTANCE	100Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	20 CYCLES
ACTUATOR LOCKING FORCE (INITIAL / 20 CYCLES)	INITIAL / 20 CYCLES 0.21N (21gf) × n MAX.
ACTUATOR UNLOCKING FORCE (INITIAL / 20 CYCLES)	INITIAL / 20 CYCLES 0.014N (1.4gf) × n MIN.
FPC RETENTION FORCE (INITIAL / AFTER TEST)	INITIAL: 0.13N (13gf) × n MIN. / AFTER TEST: 0.10N (10gf) × n MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2650
TEST REPORT	TR-20010
PACKING STANDARD	PST-15093
INSTRUCTION MANUAL	HIM-12007
APPEARANCE CRITERIA No.	QLS-A***

※ “n” IS THE NUMBER OF PIN


Custom Connectors Available

 RF
Connectors

MHF® series



Micro-coaxial/Twinax
Connectors





CABLIME® series




Wire-to-Board
Connectors/
Terminals

AP series

ISH® series




NOVASTACK® series



Board-to-Board
Connectors



I/O
Connectors





MINIDOCK™ series




FPC/FFC
Connectors

MINIFLEX® series

EVAFLEX® series



Inquiry



I-PEX, MHF, CABLINE, NOVASTACK, ISH, IARPB, MINIFLEX, EVAFLEX, MINIDOCK and ZenShield are registered trademarks of I-PEX Inc. Please note that the contents in the catalog might be changed without prior notification. I-PEX Inc. assumes no responsibility for any inaccuracies or obligation to update information on these documents. Please be sure to read and understand the latest "Precautions for Use" and "Instruction Manual" before you use our products. We shall not be responsible for any defects, damages or troubles in case you use our products without following the precautions for use. Please feel free to contact our sales representatives when you use our products for any applications that require very high reliability and safety, or that relate to human life (ex. nuclear power control, aerospace, transportation, medical equipment, safety equipment etc.).

Contact your sales representative
or more detailed information.

www.i-pex.com



I-PEX

© I-PEX Inc. 2025
All rights reserved