

MINIFLEX® 3-BFNH L-HD

0.3 mm pitch, Horizontal mating, Backflip, Hold down type, with long actuator, (height 0.9 mm)

Product Specifications:

Board Pitch	0.3 mm	
Wiping Length	Contact A: 1.0 mm	
	Contact B: 0.45 mm	
Size	Height	0.90 +/- 0.10 mm
	Width	2.1 + (0.3 x pin count) mm
	Depth	Open: 2.95 mm Close: 3.50 mm
Pin Counts	Range	7 to 71
	Available	39, 61


Applicable FPC/FFC:

FPC/FFC Contact Pitch	0.3
FPC/FFC Contact Point	Top and Bottom
FPC/FFC Thickness	0.2 +/- 0.03 mm




* Please inquire for pin counts not listed or outside of the pin count range.

▶ Hold down to improve strength of side wall



Comparison chart for side wall strength



FPC thickness t=0.20	MINIFLEX 3-BFNH L-HD TYPE (39 pin)	Company A (Front Flip 39 pin)
AVE.	22.620 N	14.162 N
MAX.	23.15 N	18.94 N
MIN.	22.25 N	10.22 N



▶ Designed with sharp edge for stronger FPC retention force

FPC Retention Force Comparison Test


FPC thickness t=0.190	Initial	Actuator operation	
		After 2 times	After 20 times
MINIFLEX 3-BFNH L-HD TYPE (39 pin)	17.432 N	16.538 N	16.052 N
Company A (Front Flip 39 pin)	10.590 N	7.900 N	6.747 N



▶ Usability for closing actuator without FPC

The connector will still function even if the actuator is accidentally closed without the FPC being inserted after the SMT process

- Connector will still function reliably (contact gap graph 39 pins before and after operating actuator without FPC inserted)





- Insertion force of connector goes up
- Retention force of connector does not change greatly

Component Parts Details





Connector Assembly

Recommended P/N 20660-0**E-01




PART No.	Pos.	A	B	C	D	E	F
◆20660-031E-01	31P	11.40	8.40	9.00	9.65	10.00	10.25
20660-039E-01	39P	13.80	10.80	11.40	12.05	12.40	12.65
20660-061E-01	61P	20.40	17.40	18.00	18.65	19.00	19.25
◆20660-071E-01	71P	23.40	20.40	21.00	21.65	22.00	22.25

◆MARK MEANS NOT AVAILABLE.



NOTE
1. CONTACT POINT: TOP AND BOTTOM CONTACT







NO.	DISCRIPTION	MATERIAL	REMARKS
5	HOLD DOWN	BRASS	
4	CONTACT(B)	PHOSPHOR BRONZE	CONTACT AREA : Au 0.1 μm MIN. OVER Ni 1.0 μm MIN. SOLDERING AREA : Au 0.03 μm MIN. OVER Ni 1.0 μm MIN.
3	CONTACT(A)	PHOSPHOR BRONZE	CONTACT AREA : Au 0.1 μm MIN. OVER Ni 1.0 μm MIN. SOLDERING AREA : Au 0.03 μm MIN. OVER Ni 1.0 μm MIN.
2	ACTUATOR	LCP	UL94V-0, BEIGE
1	HOUSING	LCP	UL94V-0, BEIGE

Connector Assembly


PART No.	Pos.	B	C	G	H
◆20660-031E-01	31P	8.40	9.00	10.40	9.60
20660-039E-01	39P	10.80	11.40	12.80	12.00
20660-061E-01	61P	17.40	18.00	19.40	18.60
◆20660-071E-01	71P	20.40	21.00	22.40	21.60

◆MARK MEANS NOT AVAILABLE.




NOTE
1. SOLDER RESIST MUST BE APPLIED TO THIS AREA.

Rev.11



CONNECTOR ON RECOMMENDED FOOTPRINT PATTERN



Connector Assembly

ITEMS	SPECIFICATION
RATING VOLTAGE	50V AC/DC (PER CONTACT PIN)
RATING AMPERAGE	0.3A DC (PER CONTACT PIN)
OPERATING TEMPERATURE	233~358K(-40°C~+85°C)
OPERATING HUMIDITY	85% MAX.
CONTACT RESISTANCE	INITIAL : 60mohm MAX. / AFTER TEST : \leq 40mohm MAX.
INSULATION RESISTANCE	100Mohm MIN.
DIELECTRIC WITHSTANDING VOLTAGE	AC250V 1min
DURABILITY	20TH CYCLES
ACTUATOR LOCKING FORCE (INITIAL / 20TH CYCLES)	INITIAL : 0.245N(24.5gf) \times n MAX. / 20TH CYCLES : 0.245N(24.5gf) \times n MAX.
ACTUATOR UNLOCKING FORCE (INITIAL / 20TH CYCLES)	INITIAL : 0.014N(1.4gf) \times n MIN. / 20TH CYCLES : 0.014N(1.4gf) \times n MIN.
FPC RETENTION FORCE (INITIAL / AFTER TEST)	INITIAL : 0.13N(13gf) \times n MIN. / AFTER TEST : 0.10N(10gf) \times n MIN.
COPLANARITY	0.10 MAX.
PRODUCT SPECIFICATION	PRS-2073
TEST REPORT	TR-15025
PACKING STANDARD	PST-15042
INSTRUCTION MANUAL	HIM-14004
APPEARANCE CRITERIA No.	QLS-A***

※ "n" IS THE NUMBER OF PIN



CAUTION


PLEASE BE SURE TO READ AND UNDERSTAND "INSTRUCTION MANUAL" BEFORE YOU USE OUR PRODUCTS.

Rev.11

Custom Connectors Available

RF Connectors

MHF® series




CABLINE® series

Micro-Coaxial/Twinaxial Connectors




Wire-to-Board Connectors/Terminals

AP series



ISH® series




NOVASTACK® series



Board-to-Board Connectors




I/O Connectors



MINIDOCK™ series

MINIFLEX® series EVAFLEX® series



FPC/FFC Connectors




Inquiry



I-PEX, MHF, CABLINE, NOVASTACK, ISH, IARPB, MINIFLEX, EVAFLEX, MINIDOCK, i-Fit and ZenShield are registered trademarks of I-PEX Inc. Please note that the contents in the catalog might be changed without prior notification. I-PEX Inc. assumes no responsibility for any inaccuracies or obligation to update information on these documents. Please be sure to read and understand the latest "Precautions for Use" and "Instruction Manual" before you use our products. We shall not be responsible for any defects, damages or troubles in case you use our products without following the precautions for use. Please feel free to contact our sales representatives when you use our products for any applications that require very high reliability and safety, or that relate to human life (ex. nuclear power control, aerospace, transportation, medical equipment, safety equipment etc.).

Contact your sales representative or more detailed information.

www.i-pex.com



I-PEX

© I-PEX Inc. 2025
All rights reserved