

CABLINE®-CA

Part No. Plug: 20633-##*T-0#S Receptacle: 20525-##*E-0##

Product Specification

Qualification Test Report No. TR-14122(P/N : 20525-0**E-0##)
TR-16023(P/N : 20525-2**E-0##)

8	S23274	September 8, 2023	H.Uchida	M.Nakamura	T.Masunaga
7	S21551	October 29, 2021	T.Ono	T.Masunaga	H.Ikari
6	S19248	April 16, 2019	Y.Sasa	T.Masunaga	Y.Shimada
5	S18687	November 1, 2018	K.Hara	T.Kurachi	Y.Shimada
Rev.	ECN	Date	Prepared by	Checked by	Approved by

1. Scope

This product specification defines the test conditions and the performances of the CABLINE-CA Connector , a wire-to-board connector of 0.4mm contact pitch.

2. Product Name and Parts No.

2.1 Product Name

CABLINE-CA

2.2 Parts No.

Plug: 20633-##*T-0#S

Receptacle: 20525-##*E-0##

3. Rating

3.1 Applicable Cable

Micro-coaxial cable ···AWG#[44、42、40、38、36]

Discrete wire ···AWG#[36、34]

Twinax cable ···AWG#[40、42]

3.2 Operating Conditions

Amperage: 0.1A AC/DC [AWG#44] (per contact / up to 60 contacts)

0.24A AC/DC [AWG#42] (per contact / up to 50 contacts)

0.3A AC/DC [AWG#40] (per contact / up to 40 contacts)

0.5A AC/DC [AWG#38] (per contact / up to 14 contacts)

0.8A AC/DC [AWG#36] (per contact / up to 6 contacts)

1.0A AC/DC [AWG#34] (per contact / up to 4 contacts)

Testing by a real machine is recommended because temperature rise may affected by actual situation.

Voltage: 100V AC (per contact)

Operating temperature: 233 to 358K(-40°C to +85°C) (Containing temperature rise by current)

Operating humidity: 85% max

3.3 Storage Conditions

Storage temperature: 248 to 333K(-25°C to 60°C)

Storage humidity: 85% max. (Non-condensing)

4. Test and Performance

Test Condition

This initial test is equal to it's at shipping condition and unless otherwise specified, all tests and measurements shall be performed under the following conditions in accordance with MIL-STD-202 G.

Temperature: 288K to 308K(15°C to 35°C)

Pressure: 866hPa to 1066hPa(650mmHg to 800mmHg)

Relative humidity: 45 to75% R.H.

4.1. Electrical Performance

1. Contact resistance	
Reference standard:	MIL-STD-202G, Method 307
Test conditions:	Solder the receptacle connector to the test board and mate the plug connector together, then measure the contact resistance as shown in Fig.1 by the four terminal methods. Apply the low level condition of 20mV MAX. DC for the open circuit voltage and 10mA MAX. DC for the closed circuit current.
<p>Fig.1</p>	
Pass criteria:	<p>Contact</p> <p>Initial: 180 mΩMAX.(AWG#34), 275 mΩMAX.(AWG#36), 360 mΩMAX.(AWG#38), 600 mΩMAX.(AWG#40), 700 mΩMAX.(AWG#42), 1080 mΩMAX.(AWG#44)</p> <p>After testing: ΔR 40 mΩ MAX.</p> <p>Initial contains the following conductor resistance of a cable 100 mm.</p> <p>100mΩMAX. (AWG#34), 195mΩMAX. (AWG#36), 280mΩMAX. (AWG#38), 520mΩMAX. (AWG#40), 620mΩMAX. (AWG#42), 1000mΩMAX.(AWG#44)</p> <p>Ground contact</p> <p>Initial: 50 mΩ MAX. After testing: ΔR 40 mΩ MAX.</p>
2. Insulation resistance	
Reference standard:	MIL-STD-202 G, Method 302
Test conditions:	Mate the plug and receptacle connector together, and then apply DC 250 V between the neighboring contacts and between contacts and SHELL.
Pass criteria:	Initial: 1000 MΩ MIN. After testing: 500 MΩ MIN.
3. Dielectric withstanding voltage	
Reference standard:	MIL-STD-202 G, Method 301
Test conditions:	Mate the receptacle and plug connector together, then apply AC 250V(rms) between the neighboring contacts and between contacts and SHELL for a minute.
Pass criteria:	No creeping discharge, flashover, no insulator breakdown shall occur.
4. Temperature rising	
Reference standard:	-
Test conditions:	Mate the plug and receptacle connector together and then apply rating current per contact.
Pass criteria:	Over ambient ΔT 30 °C MAX.

4.2. Mechanical Performance

1. Mating force and Un-mating force	
Reference standard:	-
Test conditions:	Solder the receptacle connector to the test board, then place the board and plug on push-on/pull-off machine, measure of initial and mating/un-mating 30 cycles at a speed 25±3mm/min. along the mating axis.
Pass criteria:	<p>Mating force</p> <p>10 P Initial: 7.80 N MAX. 30cycles:7.80 N MAX. 12 P Initial: 8.20 N MAX. 30cycles:8.20 N MAX. 20 P Initial: 9.70 N MAX. 30cycles:9.70 N MAX. 30 P Initial: 14.55 N MAX. 30cycles:14.55 N MAX. 40 P Initial: 19.40 N MAX. 30cycles:19.40 N MAX. 50 P Initial: 24.25 N MAX. 30cycles:24.25 N MAX. 60 P Initial: 29.10 N MAX. 30cycles:29.10 N MAX.</p> <p>Un-mating force</p> <p>10 P Initial: 1.00 N MIN. 30cycles:1.00 N MIN. 12 P Initial: 1.20 N MIN. 30cycles:1.20 N MIN. 20 P Initial: 2.00 N MIN. 30cycles:2.00 N MIN. 30 P Initial: 3.00 N MIN. 30cycles:3.00 N MIN. 40 P Initial: 4.00 N MIN. 30cycles:4.00 N MIN. 50 P Initial: 5.00 N MIN. 30cycles:5.00 N MIN. 60 P Initial: 6.00 N MIN. 30cycles:6.00 N MIN.</p>

2. Durability	
Reference standard:	-
Test conditions:	Solder the receptacle connector to the test board, then place the board and plug on the push-on/pull-off machine, and repeat mating and un-mating 30cycles at a speed 25±3mm/min. along the mating axis.
Pass criteria:	Contact resistance: Shall meet4.1.1

3. Contact retention force	
Reference standard:	-
Test conditions:	Place the connector on the push-on/pull-off machine, then apply force on the contact head and push the contact along the direction opposite to the contact insertion at a speed of 25±3mm/min. Measure the force when the contact dislodges the connector.
Pass criteria:	Plug contact retention force: 0.60N MIN. Receptacle contact retention force: 0.20N MIN.

4. Conn. Lock	
Reference standard:	-
Test conditions:	Mate, and place them on the push-on/pull-off machine, then apply 10N force on the cable along the mating axis.
Pass criteria:	The lock does not damage and cancel.

4.2. Mechanical Performance

5. Cable retention force	
Reference standard:	-
Test conditions:	Place the plug connector on the push-on/pull-off machine and then apply force on the cable along the direction at a speed 25±3mm/min. Measure the force when the cable dislodges the plug connector.
Pass criteria:	10P: 4.90 N MIN. 12P: 5.88 N MIN. 20P: 9.80 N MIN. 30P: 14.70 N MIN. 40P: 19.60 N MIN. 50P: 24.50 N MIN. 60P: 29.40 N MIN.

6. Vibration	
Reference standard:	MIL-STD-202 G, Method 201A
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and place them on the vibrator. Then apply the following vibration. During the testing, run 100mA DC to check electrical discontinuity. Frequency: 10Hz→55Hz→10Hz/approx. 1min. Directions: 3 mutually perpendicular direction. Total Amplitude: 1.52mm Sweep duration: 2 hours for each direction, a total of 6 hours.
Pass criteria:	Contact resistance: Shall meet 4.1.1. Electrical discontinuity: No electrical discontinuity greater than 1µs shall occur. Appearance: No abnormality adversely affecting the performance shall occur.

7. Shock	
Reference standard:	MIL-STD-202 G, Method 213B, Condition A.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and place them on the shock machine. Then apply the following shock. MAX.G: 50G Duration: 11msec Wave Form: Half Sinusoidal Directions: 6 mutually perpendicular direction Cycle: 3 cycles about each direction
Pass criteria:	Contact resistance: Shall meet 4.1.1. Electrical discontinuity: No electrical discontinuity greater than 1µs shall occur. Appearance: No abnormality adversely affecting the performance shall occur.

4.3. Environmental Performance

1. Thermal shock	
Reference standard:	MIL-STD-202 G, Method 107G, Condition A.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: 218K(-55°C),30min.→358K(85°C),30min. Transition time: 5min. MAX. No. of cycles: 5 cycles
Pass criteria:	Contact resistance: Shall meet 4.1.1. Appearance: No abnormality adversely affecting the performance shall occur.

2. High temperature life	
Reference standard:	MIL-STD-202 G, Method 108A, Condition B.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: 358±2K (85±2°C) Duration: 250 hours
Pass criteria:	Contact resistance: Shall meet 4.1.1. Contact retention force: Shall meet 4.2.3. Appearance: No abnormality adversely affecting the performance shall occur.

3. Humidity (Steady state)	
Reference standard:	MIL-STD-202 G, Method 103B, Condition A.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: 313±2K (40±2°C) Humidity: 90~95%RH Duration: 240 hours
Pass criteria:	Contact resistance: Shall meet 4.1.1. Insulation resistance: Shall meet 4.1.2. Dielectric withstanding voltage: Shall meet 4.1.3. Appearance: No abnormality adversely affecting the performance shall occur.

4. Humidity (Cycling)	
Reference standard:	MIL-STD-202 G, Method 106G.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: 298[263]~338K (25[-10]~65°C) Humidity: 90~98%RH Duration: 10cycles (240hours)
Pass criteria:	Contact resistance: Shall meet 4.1.1. Insulation resistance: Shall meet 4.1.2. Dielectric withstanding voltage: Shall meet 4.1.3. Appearance: No abnormality adversely affecting the performance shall occur.

4.3. Environmental Performance

5. Saltwater spray

Reference standard:	MIL-STD-202 G, Method 101E, Condition B.
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: $308 \pm 2\text{K}$ ($35 \pm 2^\circ\text{C}$) Saltwater density: $5 \pm 1\%$ [by weight] Duration: 48 hours
Pass criteria:	Contact resistance: Shall meet 4.1.1. Appearance: No abnormality adversely affecting the performance shall occur.

6. H₂S gas

Reference standard:	-
Test conditions:	Solder the receptacle connector to the test board, then mate plug connector, and expose them to the following environment. Temperature: $313 \pm 2\text{K}$ ($40 \pm 2^\circ\text{C}$) Relative humidity: $80 \pm 5\%$ RH Gas: H ₂ S 3 ± 1 ppm Duration: 96 hours
Pass criteria:	Contact resistance: Shall meet 4.1.1. Appearance: No abnormality adversely affecting the performance shall occur.

4.4. Others

1. Solder ability	
Reference standard:	-
Test conditions:	Dip the solder tine of the contact in the solder bath at $518 \pm 5K$ ($245 \pm 5^{\circ}C$) for 5 ± 0.5 seconds after immersing the tine in the flux of RMA or R type for 5 to 10 seconds.
Pass criteria:	More than 95% of the dipped surface shall be evenly wet.

2. Soldering heat resistance	
Reference standard:	-
Test conditions:	<p>Reflow: Reflow temperature as shown in Fig.2. The number of times of Reflow is within 2.</p> <p>Soldering iron: Operating temperature : $613 \sim 633K$ ($350^{\circ}C \pm 10$)</p> <p>Application time of soldering iron : 5 ± 1 sec.</p> <p>The number of times of application : 3times</p>
<p>Fig.2</p>	
Pass criteria:	No abnormality adversely affecting the performance shall not occur.

4.5 Test Sequence and Specimen Quantity

Table.1 Test Sequence and Sample Quantity

Test Item	Group												
	A	B	C	D	E	F	G	H	J	K	L	M	N
Contact Resistance	2,6			1,3,5	1,3	1,3	1,5	1,5,7	1,3	1,3			
Insulation Resistance							2,6	2,8					
D. W. Voltage							3,7	3,9					
Temp. Life													1
Mating Force	1,5												
Un-mating Force	3,7												
Durability	4							4 (10cycles)					
Contact Retention Force		1,3											
Conn. Lock			1										
Cable Retention Force	8												
Vibration				2									
Shock				4									
Thermal Shock					2								
High Temperature Life		2				2							
Humidity (Steady State)							4						
Humidity (Cycling)								6					
Salt Water Spray									2				
H2S Gas										2			
Solder ability											1		
Soldering Heat Resistance												1	
Sample QTY.	5 pcs.	20 pcs.	5 pcs.	5 pcs.	5 pcs.	5 pcs.	5 pcs.	5 pcs.	5 pcs.	5 pcs.	10 pcs.	10 pcs.	5 pcs.

※Numbers indicate test sequences.

5. Recommended Metal Mask

Recommended thickness of METAL MASK : t=0.12
 Recommended Opening ratio of METAL MASK : 100%
 *The pattern dimensions refer to a drawing

6. Precautions for Handling Cable Connectors

Refer to instruction manual : HIM-09008 for the handling of CABLINE-CA.